



PRODUCT FACT SHEET

TLR-1 HL[®] HIGH LUMEN RAIL MOUNTED STROBING TACTICAL LIGHT

MARKET

APPLICATIONS: Law Enforcement, Security, Military, Home Defense

DESCRIPTION: Lightweight, compact, high lumen lithium battery powered Gun-Mounted Tactical Light featuring the latest in shock-proof power LED technology and providing 1.75 hours of continuous run time. Tethered battery door and latch mechanism prevents battery door loss while providing easy battery replacement. Rail clamp designed to rapidly attach/detach from side of weapon. When enabled, strobe activated on two or more momentary paddle hits.

CASE MATERIAL: 6000 Series machined aircraft aluminum with black anodized finish.

DIMENSIONS: Length: 3.39 in. (8.61 cm) Width: 1.47 in. (3.73 cm) Height: 1.44 in. (3.65 cm)

WEIGHT: 4.18 oz (118.6 grams) with batteries (included in purchase).

LENS: High temperature, shock mounted, impact resistant Boro Float glass.

LIGHT SOURCE: C4[®]LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: 15,000 candela peak beam intensity, 245m beam distance, 800 lumens measured system output. TIR optic produces a concentrated beam with optimum peripheral illumination.

ON/OFF: Ambidextrous momentary/steady On-Off switch.
Double tap of momentary paddle within 0.4 seconds activates strobe.
Strobe can be disabled.

RUN TIME: 1.25 hours of regulated run time and 1.75 hours to 10% output.
Solid-state current regulation for consistent illumination level.

BATTERY: Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.

FEATURES: C4[®]LED technology for extreme brightness.
Ambidextrous momentary/steady On-Off switch.
One handed snap-on & tighten interface keeps hands away from muzzle when attaching/detaching.
Securely fits a broad range of weapons.
Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails.
Includes keys for Glock-style, Picatinny, Beretta 90two, S&W 99 and S&W TSW.
Extensively live-fire tested impact resistant construction.
Operating temperature: -40°F to +120°F.
IPX7 rated design; waterproof to 1 meter for 30 minutes.
Strobe can be disabled.

APPROVALS: Meets applicable European Community Directives. **CE**

WARRANTY: Streamlight's Limited Lifetime Warranty.

OPTIONAL

ACCESSORIES: Mounting Adapters, Remote Switches, Filters