

SL-20X® LED RECHARGEABLE FLASHLIGHT



Case Material: Machined aircraft-grade aluminum with anodized finish

Dimensions/ Length: 13.2 in. (33.53 cm) Diameter: Major Diameter: 2.5 in. (6.35 cm) Body Diameter: 1.50 in. (3.81 cm)
 Weight: 1.7 lbs. (.77 kg)

Lens: Unbreakable polycarbonate lens with scratch-resistant coating

Light Source: 10-watt, 6-volt halogen bulb with 100 hour lifetime 3 high intensity LEDs with 100,000 hour lifetime

Light Output: 38,000 candela (peak beam intensity)
 Bulb Rating - 200 lumens
 LED Rating - 30 lumens

On/Off: Lifetime dual-switch control for halogen and LEDs Momentary and constant on for halogen Constant on for LEDs

Run Time: Halogen only -80 minutes
 LEDs only - 40 hours
 Emergency back up LED (after full halogen run) - 1 hour minimum

Battery/ Rechargeable nickel-cadmium battery can be recharged up to 1,000 times on AC or 12V DC 10 hour overnight
 Charging: charger-holder

- Features:
- Power Failure Feature: with the light in the “On” position in the charger, if there is a power failure, the light will automatically illuminate
 - O-ring sealed for water resistance
 - Serialized for positive identification

Approvals: Most models meet applicable European Community Directives

Warranty: Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Part #
SL-20X-LED IEC Type C (230V) AC/DC - 2 Sleeves	080926-20205-4	20205
SL-20X-LED 240V AC/DC - 2 Sleeves	080926-20208-5	20208
SL-20X-LED 120V AC/DC - 2 Sleeves	080926-20203-0	20203
SL-20X-LED IEC Type A (100V) AC/DC - 2 Sleeves	080926-20210-8	20210
SL-20X-LED IEC Type C (230V) AC	080926-20204-7	20204
SL-20X-LED 240V AC	080926-20206-1	20206
SL-20X-LED 120V AC	080926-20201-6	20201
SL-20X-LED IEC Type A (100V)	080926-20209-2	20209
SL-20X-LED 12V DC	080926-20202-3	20202
SL-20X-LED - (WITHOUT CHARGER)	080926-20200-9	20200
<i>See reverse for additional part numbers</i>		



Item	UPC	Part #
Charge Sleeve Assembly (Cord not included)	080926-22052-2	22052
DC2 direct wire charge cord	080926-22050-8	22050
DC1 Charge Cord	080926-22051-5	22051
120V AC charge cord	080926-22311-0	22311
Type A (/120V) AC charge cord	080926-22060-7	22060
Type C (230V) AC charge cord	080926-22061-4	22061
240V AC charge cord	080926-22241-0	22241
5 Unit Bank Charger, 120V	080926-21400-2	21400
5 Unit Bank Charger DC	080926-21401-9	21401
Battery Stick (NiCd)	080926-20175-0	20175
Lamp Module*	080926-20111-8	20111
Lens (Clear polycarbonate)*	080926-20160-6	20160
Safety Wand Red	080926-22511-4	22511
Safety Wand Blue	080926-22512-1	22512
Safety Wand Glow in the Dark	080926-22513-8	22513
Safety Wand White	080926-22517-6	22517
Safety Wand Yellow	080926-22519-0	22519
Ring Holder	080926-22911-2	22911
Holster, SL Series (Nylon)	080926-25090-1	25090

*Not pictured



STREAMLIGHT



30 Eagleville Road • Eagleville, PA 19403 • 610-631-0600/800-523-7488 Phone • 610-631-0712/800-220-7007 Fax
 www.streamlight.com ©Streamlight SL-20X LED 12/15