



**ProTac® Rail Mount 2**  
**HIGH LUMEN RAIL MOUNTED STROBING TACTICAL LIGHT**

**MARKET**

**APPLICATIONS:** Law Enforcement, Security, Military, Home Defense

**DESCRIPTION:** Lightweight, compact, low profile, high lumen, lithium battery powered Gun-Mounted Tactical Light featuring the latest in shock-proof power LED technology and providing two hours of continuous run time on high and over 20 hours on low intensity. Rail clamp designed to rapidly and securely attach/detach from rifles, carbines and submachine guns with a MIL Standard 1913 Rail.

**CASE MATERIAL:** 6000 Series machined aircraft aluminum with black anodized finish.

**DIMENSIONS:** Length: 5.00 in. (12.7 cm)      Width: 1.20 in. (3.04 cm)      Height: 1.50 in. (3.81 cm)

**WEIGHT:** 5.0 oz (141.7 grams) with batteries (included in purchase).

**LENS:** High temperature, shock mounted, AR coated, impact resistant Boro Float glass.

**LIGHT SOURCE:** C4®LED technology, impervious to shock with a 50,000 hour lifetime.

**LIGHT OUTPUT:** High: 22,000 candela peak beam intensity, 297m beam distance, 625 lumens measured system output. Low: 2,000 candela peak beam intensity, 89m beam distance, 60 lumens measured system output.

TIR optic produces a concentrated beam with optimum peripheral illumination.

**ON/OFF:** Multi-function, push-button tactical tail switch or Dual remote pressure switch with latching push button. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe (factory default), high only, or low/high.

**RUN TIME:** High: 1.5 hours of regulated run time and 2 hours to 10% output. Low: 18 hours of regulated run time and 21 hours to 10% output. Solid-state current regulation for consistent illumination level.

**BATTERY:** Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.

**FEATURES:** C4®LED technology for extreme brightness.  
Momentary/steady On-Off switch.  
One handed snap-on & tighten interface keeps hands away from muzzle when attaching/detaching.  
Securely fits a broad range of weapons.  
Mounts directly to guns with MIL-STD-1913 (Picatinny) rails.  
Extensively live-fire tested, impact resistant construction.  
Operating temperature: -40°F to +120°F.  
IPX7 rated with the Standard button switch installed; waterproof to 1 meter for 30 minutes.  
IPX4 rated with the Remote Pressure Switch installed.

**APPROVALS:** Meets applicable European Community Directives. **CE**

**WARRANTY:** Streamlight's Limited Lifetime Warranty.

**OPTIONAL ACCESSORIES:** Red, Blue, and Green Filters