



TLR-2 HL®

HIGH LUMEN RAIL MOUNTED STROBING TACTICAL LIGHT WITH LASER SIGHT

MARKET

APPLICATIONS: Law Enforcement, Security, Military, Home Defense

DESCRIPTION: Lightweight, compact, high lumen lithium battery powered Gun-Mounted Tactical Light with integrated aiming laser featuring the latest in shock-proof power LED technology and providing 1.75 hours of continuous run time when in dual mode with the high power visible laser. Tethered battery door and latch mechanism prevents battery door loss while providing easy battery replacement. Rail clamp designed to rapidly attach/detach from side of weapon. When enabled, strobe activated on two or more momentary paddle hits.

CASE MATERIAL: 6000 Series machined aircraft aluminum with black anodized finish on main body. High impact, chemically resistant engineering polymer laser housing.

DIMENSIONS: Length: 3.39 in. (8.61 cm) Width: 1.47 in. (3.73 cm) Height: 1.83 in. (4.64 cm)

WEIGHT: 4.78 oz (135.5 grams) with batteries (included in purchase).

LENS: High temperature, shock mounted, impact resistant Boro Float glass.

LIGHT SOURCE: C4®LED technology, impervious to shock with a 50,000 hour lifetime. 640-660nm red laser.

LIGHT OUTPUT: 15,000 candela peak beam intensity, 245m beam distance, 800 lumens measured system output. TIR optic produces a concentrated beam with optimum peripheral illumination. Laser provides long-range targeting.

ON/OFF: Ambidextrous momentary/steady On-Off switch.
Three position Mode Selector switch (Laser only, LED Illumination only, both)
Double tap of momentary paddle within 0.4 seconds activates strobe.
Strobe can be disabled.

RUN TIME: 1.25 hours regulated run time and 1.75 hours to 10% output when using Laser/LED simultaneously. 45 hours of run time when using Laser only.
Solid-state current regulation for consistent illumination level.

BATTERY: Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.

FEATURES: C4®LED technology for extreme brightness.
Ambidextrous momentary/steady On-Off switch.
One handed snap-on & tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons.
Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails. Includes keys for Glock-style, Picatinny, Beretta 90two, S&W 99 and S&W TSW.
Extensively live-fire tested impact resistant construction.
Windage and Elevation adjustment screws mounted in brass bushings for long life and dependable zero retention.
Highly accurate sight repeatability when remounting.
Operating temperature: -40° F to +120° F.
IPX4 rated design for water resistant operation.
Strobe can be disabled.

APPROVALS: Meets applicable European Community Directives. **CE**

WARRANTY: Streamlight's Limited Lifetime Warranty.

OPTIONAL

ACCESSORIES: Mounting Adapters, Remote Switches, Filters

EXPORT CONTROLS: The export of this product is subject to the jurisdiction of the U.S. Department of Commerce Export Administrative Regulations ("EAR"). The exported sale, transfer or shipment of this product is expressly prohibited by U.S. Law and is subject to export restrictions, including export licenses and accompanying documentation and authorization, the absence of which may result in fines and penalties. Furthermore, diversion, resale, re-export or transfer of this product is contrary to U.S. Law and is prohibited without the prior written consent of the U.S. Department of Commerce. Compliance with any and all export controls are the sole responsibility of the distributor.

Issued: 10/29/2012

Revised: 09/16/2015 Rev: 2

Assembled in the U.S.A.

Document #260