

SL-20L® FULL SIZE RECHARGEABLE LED FLASHLIGHT

FL1 STANDARD	HIGH	MEDIUM	LOW
	350 LUMENS	160 LUMENS	10 LUMENS
	2h	4h	50h
	490m	329m	63m
	60,000cd	27,000cd	1,000cd

Strobe: runs 4 hours



Case Material/ Machined aircraft-grade aluminum with type II anodized finish. Available in black.

Lens: Unbreakable polycarbonate lens with scratch-resistant coating. O-ring sealed

Dimensions/ 13.1 in. (33.3 cm) Diameter: Major Diameter: 2.50 in. (6.35 cm)

Weight: 1.7 lb. (.77 kg) with battery

Light Source: C4® LED technology, impervious to shock with a 50,000 hour lifetime. Deep-dish parabolic reflector produces a tight beam with optimal peripheral illumination to aid in navigation

Light Output/ High: 60,000 candela peak beam intensity; 350 lumens; runs 2 hours

Run time: Medium: 27,000 candela peak beam intensity; 160 lumens; runs 4 hours

Low: 1,000 candela peak beam intensity; 10 lumens; runs 50 hours

Strobe: runs 4 hours

On/Off: Multi-function, push-button barrel switch. One handed operation of momentary, variable intensity or strobe mode

Battery: 5-cell, 6.0 Volt Ni-Cd sub-C battery, rechargeable up to 1000 times

5-cell, 6.0 Volt Ni-MH sub-C battery, rechargeable up to 1000 times

Charging: Illuminated switch housing indicates charge status; steady for charging and blinking for charging complete. 7 hour battery recharge time. Fits existing charger-holders, available with AC or 12V DC charge cords.

Features: IPX4 rated design; water resistant operation.

1 meter impact resistance tested.

Serialized for positive identification.

Approvals: Meets applicable European Community directives.

Warranty: Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Part #
SL-20L with IEC Type C (230V) AC/DC - 2 Sleeves NiMH	080926-20705-9	20705
SL-20L with 240V AC/DC - 2 Sleeves NiMH	080926-20707-3	20707
SL-20L with 120V AC/DC - 2 Sleeves NiCd	080926-20603-8	20603
SL-20L with 120V AC/DC - 2 Sleeves NiMH	080926-20703-5	20703
SL-20L with IEC Type A (100V) AC/DC - 2 Sleeves NiMH	080926-20709-7	20709
SL-20L with IEC Type C (230V) AC NiMH	080926-20704-2	20704
SL-20L with 240V AC NiMH	080926-20706-6	20706
SL-20L with 120V AC NiCd	080926-20601-4	20601
SL-20L with 120V AC NiMH	080926-20701-1	20701
SL-20L with IEC Type A (100V) AC NiMH	080926-20708-1	20708
SL-20L with 12V DC NiCd	080926-20202-3	20602
SL-20L with 12V DC NiMH	080926-20702-8	20702
SL-20L NiCd - (WITHOUT CHARGER)	080926-20600-7	20600
SL-20L NiMH - (WITHOUT CHARGER)	080926-20700-4	20700



Item	UPC	Part #
Charge Sleeve Assembly (Cord not included)	080926-22052-2	22052
DC2 direct wire charge cord	080926-22050-8	22050
DC1 Charge Cord	080926-22051-5	22051
120V AC charge cord	080926-22311-0	22311
Type A (100V/120V) AC charge cord	080926-22060-7	22060
Type C (230V) AC charge cord	080926-22061-4	22061
240V AC charge cord	080926-22241-0	22241
5 Unit Bank Charger, 120V	080926-21400-2	21400
5 Unit Bank Charger DC	080926-21401-9	21401
Battery Stick (NiCd)	080926-77175-8	77175
Battery Stick (NiMH)	080926-77375-2	77375
Safety Wand Red	080926-22511-4	22511
Safety Wand Blue	080926-22512-1	22512
Safety Wand Glow in the Dark	080926-22513-8	22513
Safety Wand White	080926-22517-6	22517
Safety Wand Yellow	080926-22519-0	22519
Ring Holder	080926-22911-2	22911
Holster, SL Series (Nylon)	080926-25090-1	25090

