

TRIDENT® LED HEADLAMP

ALKALINE AAA BATTERY-POWERED HEADLAMP

MARKET
APPLICATIONS:

Outdoor, Sporting Goods, Automotive, Hardware/Do-It-Yourself, Industrial, Emergency Medical Services, Safety, Gift, Consumer, Pest Control, Boating

DESCRIPTION:

The Trident® headlamp with adjustable elastic head strap features a single C4® power LED with three Ultra Bright 5mm LEDs for long and close distance light in one package. The light offers 3 position lighting in the configurations listed.

a. The Yellow model contains three (3) Ultra Bright White 5mm LEDs, and a C4® power LED.

b. The Green model contains one (1) Green 5mm LED, two (2) White 5mm LEDs, and a C4® power LED.

All models are equipped with a low battery warning indicator.

CASE MATERIAL:

Tough ABS thermoplastic construction with elastomer over mold. Available in Yellow or Green.

DIMENSIONS:

Face Cap Diameter: 1.75 in. (4.45cm) Maximum Width: 2.70 in (6.85 cm)

Maximum Depth (including head strap mounting plate): 2.40 in. (6.09 cm)

WEIGHT:

5.50 oz (156.0 grams) with batteries (included with purchase).

LENS:

Unbreakable polycarbonate lens.

LIGHT SOURCE:

All models - One (1) White C4® LED technology, impervious to shock with a 50,000 hour lifetime.

Yellow Model - Three (3) 5mm Ultra Bright White LEDs, impervious to shock with 100,000 hour lifetime.

Green Model - One (1) 5mm Ultra Bright Green LED, Two (2) 5mm Ultra Bright White LEDs, impervious to shock with 100,000 hour lifetime.

LIGHT OUTPUT:

See charts for specific model.


ON/OFF:

Push-button sequence through modes:

Yellow model - One (1) 5mm LED, Three (3) 5mm LEDs, C4 power LED, and Off.

Green Model - One (1) 5mm Green LED, Two (2) 5mm White LEDs, C4 power LED, and Off.

RUN TIME:


See charts for specific model. All claims to 10% of initial lumen output.

BATTERY:

Three (3) "AAA" size, Alkaline batteries.

FEATURES:


C4® LED technology for extreme brightness.

Low Battery Indicator - Red LED flashes when battery voltage is low and batteries are near the end of their usable life. LED is located in the reflector in between the "Low Batt" marking and functions while the light is energized.

IPX4 rated for water resistant operation.

2 meter impact resistance tested.

90 degree tilting head.

Rubber Hard Hat Strap (included in purchase).

WARRANTY:

Streamlight's Limited Lifetime Warranty

APPROVALS:


Class 1, Division 2, Groups A,B,C,D; Class II, Division 2, Groups F,G; Class III, Temp Code: T5



Meets applicable European Community directives.

OPTIONAL
ACCESSORIES:

N/A

OUTPUT
RUNTIME
DISTANCE
INTENSITY

	YELLOW BODY			
	FL1 STANDARD	C4 LED	3 LED	1 LED
		80 LUMENS	35 LUMENS	11 LUMENS
		5h	10h	53h
		126m	39m	22m
		4000cd	385cd	120cd

	GREEN BODY			
	FL1 STANDARD	C4 LED	2 LED	1 LED
		80 LUMENS	25 LUMENS	6 LUMENS
		5h	19h 30m	63h
		126m	33m	15m
		4000cd	275cd	55cd